


Disposable Gloves

pronotice®

Product Overview	Nitrile Gloves					Vinyl Gloves				Latex Gloves		
	Light	Regular		Heavy		Light	Regular		Light	Regular	Heavy	
Specifications												
Weight	3.0 gr (+/- 0.3)	3.5 gr (+/- 0.3)	4.0 gr (+/- 0.3)	4.5 gr (+/- 0.3)	5.0 gr (+/- 0.3)	4.0 gr (+/- 0.3)	4.5 gr (+/- 0.3)	5.0 gr (+/- 0.3)	5.5 gr (+/- 0.3)	5.0 gr (+/- 0.3)	5.5 gr (+/- 0.3)	6.0 gr (+/- 0.3)
Length (mm)	240mm	240mm	240mm	240mm	240mm	240mm	240mm	240mm	240mm	240mm	240mm	240mm
Powdered / Powder Free	Powder free	Powder free	Powder free	Powder free	Powder free	Both available	Both available	Both available	Both available	Both available	Both available	Both available
Exterior / Surface	Finger textured	Finger textured	Finger textured Full textured	Finger textured Full textured	Finger textured	Smooth	Smooth	Smooth	Smooth	Finger textured	Finger textured	Finger textured
Thickness at palm (mm)	0.05mm (+/-0.2)	0.06mm (+/-0.2)	0.07mm (+/-0.2)	0.08mm (+/-0.2)	0.09mm (+/-0.2)	0.06mm (+/-0.2)	0.07mm (+/-0.2)	0.08mm (+/-0.2)	0.09mm (+/-0.2)	0.08mm (+/-0.3)	0.08mm (+/-0.3)	0.08mm (+/-0.3)
MDR CE Class	Class I	Class I	Class I	Class I	Class I	-	Class I	Class I	Class I	Class I	Class I	Class I
PPE / Risk Cat	Class III (TYPE C)	Class III (TYPE C)	Class III (TYPE B)	Class III (TYPE B)	Class III (TYPE B)	Class III (TYPE C)	Class III (TYPE C)	Class III (TYPE C)	Class III (TYPE C)	Class III	Class III	Class III
Colors available	Black Cobalt Blue	Light Blue Lilac Blue Cobalt blue Purple Pink Black White	Light Blue Lilac Blue Cobalt blue Purple Pink Black White	Light Blue Black	Light Blue Black	Clear	Clear Creamy White	Clear Creamy White	Clear Creamy White	Natural	Natural	Natural
AQL	AQL 1.5	AQL 1.5	AQL 1.5	AQL 1.5	AQL 1.5	-	AQL 1.5	AQL 1.5	AQL 1.5	AQL 1.5 AQL 4.0	AQL 1.5 AQL 4.0	AQL 1.5 AQL 4.0
Suitable for food contact	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✗	✗
Suitable for general protection	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✗	✗
Suitable for beauty, fashion, estheticians	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✗	✗
EN test approved	-	EN 445 EN 420 EN 374-2 EN 374-3 EN 16523-1	EN 445 EN 420 EN 374-2 EN 374-3 EN 16523-1	EN 445 EN 420 EN 374-2 EN 374-3 EN 16523-1	EN 445 EN 420 EN 374-2 EN 374-3 EN 16523-1	-	EN 445 EN 420 EN 374-2 EN 374-3 EN 16523-1	EN 445 EN 420 EN 374-2 EN 374-3 EN 16523-1	EN 445 EN 420 EN 374-2 EN 374-3 EN 16523-1	-	EN 455 EN 374-2	EN 455 EN 374-2

Values might vary in an acceptable range that will still guarantee the glove efficient performance.